



Pro Audio  
Germany

# PCS - T SERIES

[www.4-acoustic.com](http://www.4-acoustic.com)

PCS-T is our premium full-range speaker series in high end quality. The exclusive use of high-standard components and an excellent workmanship could define the PCS-T series as perfect. From the technical side, we have deliberately tuned this series to not sound aggressive and given the speaker components the acoustical space they need to be transparent and natural. All four models are equipped with precisely tuned crossovers networks. The sound calibration of this series has transparent and clearly differentiated mid/high frequencies which provide a harmonious sound even at very high sound pressure levels. The workmanship is made without any compromises. The selection of the wood, varnish and speaker components is focused exclusively on the construction of a unique perfect sound speaker. All speakers of the PCS-T series have a VSL flight frame mounting base for wall, ceiling and truss installation, as well as various attachment points for hanging.

## PCS - T SERIES





# Contents

Contents.....	<b>03</b>
PCS-108T 8" + 1" Two Way Full Range Speaker .....	<b>04</b>
PCS-110T 10" + 1" Two Way Full Range Speaker .....	<b>05</b>
PCS-112T 12" + 1,4" Two Way Full Range Speaker .....	<b>06</b>
PCS-115T 15" + 1,4" Two Way Full Range Speaker .....	<b>07</b>

# PCS-108T

www.4-acoustic.com

- Crafted with the high quality components
- Suitable for touring, rental and installation
- 500 W program power
- 250 W AES power
- Anti-scratch Polyurethane coating
- Connecting panel with Neutrik NL4 sockets
- 8 Ohm Impedance
- Proprietary 90° x 40° horn design



## Specification

### PCS-108T

Model Name	PCS-108T
GS1 (EAN) CODE	4260318510257
System Type	2-Way 8"+1" Fullrange Speaker
Power Rating	250 W AES 500 W program 1000 W peak
Frequency Range (+/- 3 dB)	53 Hz - 20 kHz
Coverage Pattern (hvx)	90°x40°
Sensitivity	97 dB 1w/1m
Maximum SPL	127 dB
Woofer	1 x STG-08T
Driver	1 x STG-44R
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Suspension/Mounting	VESA 75 (Backside) 35 mm pole socket 16 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	450x279x276 mm
Net weight	14,7 kg

## Accessories

### PCS-108T

Order Code	GS1 (EAN) Code	Type
PCS-108T-RC	4260318511421	Rain and transport cover for PCS-108T
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm
SA-2080	4260318510820	2 Channel Class H Amplifier 2 x 800 Watt @ 8 ohm





**Pro Audio**  
Germany

# PCS-110T

www.4-acoustic.com

- Crafted with the high quality components
- Designed for touring, rental and installation
- 600 W program power
- 300 W AES power
- Anti-scratch Polyurethane coating
- Connecting panel with Neutrik NL4 sockets
- 8 Ohm Impedance
- Proprietary 90° x 40° linear directivity horn design



## Specification

### PCS-110T

Model Name	PCS-110T
GS1 (EAN) CODE	4260318510264
System Type	2-Way 10"+1" Fullrange Speaker
Power Rating	300 W AES 600 W program 1200 W peak
Frequency Range (+/- 3 dB)	49 Hz - 20 kHz
Coverage Pattern (hvx)	90°x40°
Sensitivity	98 dB 1w/1m
Maximum SPL	128 dB
Woofer	1 x STG-10T
Driver	1 x STG-44R
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Suspension/Mounting	VESA 75 (Backside) 35 mm pole socket 16 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	510x315x322 mm
Net weight	18,6 kg

## Accessories

### PCS-110T

Order Code	GS1 (EAN) Code	Type
PCS-110T-RC	4260318511438	Rain and transport cover for PCS-110T
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm
SA-2080	4260318510820	2 Channel Class H Amplifier 2 x 800 Watt @ 8 ohm



**GERMAN**  
**Pro**  
**Audio**  
Engineering

# PCS-112T

www.4-acoustic.com

- Highest quality birch multiplex wood
- Suitable for touring, rental and installation
- 1000 W program power
- 500 W AES power
- 18 x M8 suspension
- 1,4" compression driver with 3" voice coil
- 8 Ohm Impedance
- Proprietary 90° x 40° horn design

## Specification

### PCS-112T



Model Name	PCS-112T
GS1 (EAN) CODE	4260318510271
System Type	2-Way 12"+1,4" (3" voice coil) Fullrange Speaker
Power Rating	500 W AES 1000 W program 2000 W peak
Frequency Range (+/- 3 dB)	41 Hz - 20 kHz
Coverage Pattern (h xv)	90°x40°
Sensitivity	101 dB 1w/1m
Maximum SPL	133 dB
Woofers	1 x STG-12T
Driver	1 x STG-75B, 3" voice coil
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Suspension/Mounting	35 mm pole socket 18 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	620x386x405 mm
Net weight	26,8 kg

## Accessories

### PCS-112T

Order Code	GS1 (EAN) Code	Type
PCS-112T-RC	4260318511445	Rain and transport cover for PCS-112T
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm
SA-2100	4260318510837	2 Channel Class H Amplifier 2 x 1000 Watt @ 8 ohm





**Pro Audio**  
Germany

## PCS-115T

[www.4-acoustic.com](http://www.4-acoustic.com)

- Crafted with the highest quality components
- Suitable for touring, rental and installation
- 1200 W program power
- 600 W AES power
- 18 x M8 suspension
- 1,4" compression driver with 3" voice coil
- 8 Ohm Impedance
- Proprietary 90° x 40° horn design



### Specification

#### PCS-115T

Model Name	PCS-115T
GS1 (EAN) CODE	4260318510288
System Type	2-Way 15"+1,4" (3" voice coil) Fullrange Speaker
Power Rating	600 W AES 1200 W program 2400 W peak
Frequency Range (+/- 3 dB)	39 Hz - 20 kHz
Coverage Pattern (hvx)	90°x40°
Sensitivity	103 dB 1w/1m
Maximum SPL	136 dB
Woofer	1 x STG-15T
Driver	1 x STG-75B, 3" voice coil
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/-1-
Suspension/Mounting	35 mm pole socket 18 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	700x450x490 mm
Net weight	38,1 kg

### Accessories

#### PCS-115T

Order Code	GS1 (EAN) Code	Type
PCS-115T-RC	4260318511452	Rain and transport cover for PCS-115T
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm
SA-2130	4260318510844	2 Channel Class H Amplifier 2 x 1300 Watt @ 8 ohm



**GERMAN**  
**Pro**  
**Audio**  
Engineering



**Pro Audio**  
Germany

# PCS - T SERIES

[www.4-acoustic.com](http://www.4-acoustic.com)

# PCS - T SERIES



**Pro Audio**  
Germany

**INLINE Marketing GmbH**

Bunsenstrasse 32

59229 Ahlen, Germany

Tel. +49 2382 7087-0

Fax +49 2382 7087-25

E-Mail [sales@4-acoustic.com](mailto:sales@4-acoustic.com)

Web [www.4-acoustic.com](http://www.4-acoustic.com)